Access XL2/XXL

Access barriers for wide lanes





For particularly wide lanes

For entrances to freight forwarders, company and port facilities, as well as on multi-lane roads – Magnetic XL2 and XXL barriers are the ideal solution when wide entrances of up to 8.5 m (XL2) and up to 10 m (XXL) have to be controlled with a single barrier. An optional boom skirt also efficiently prevents intruders in security-relevant areas. With their low impact forces, these barriers are also approved for locations where the movement of people can be expected (when the stipulated safety equipment is installed).

At the heart of the Access series is the innovative MHTM[™] drive that is distinguished by its energy efficiency, lack of maintenance and long service life – the Access XL2 and XXL are designed for 2 million opening and closing cycles. By the way, Magnetic quality lies not just in the detail, but is also easily recognisable to all thanks to stylish design. The Access series has already been awarded two design prizes.



For wide entrances With maximum barrier widths of 8.5 m and 10 m respectively, the Access XL2 and the Access XXL are the ideal solution for wide entrances that have to be controlled with a single barrier.



Innovative drive technology The MHTM[™] drive unit is maintenancefree, energy-efficient and quiet. The high torque guarantees best possible operation even under extreme weather conditions.



Legal security

All Magnetic barriers have a Declaration of Conformity in compliance with the Machinery Directive and a Declaration of Performance in line with the Construction Products Directive. Thus operators and those responsible for commissioning are always on the safe side in questions of liability.



Easy access to components Two simple steps: control systems and the drive unit are easily reached by removing the cover and front plate. This increases user-friendliness and accelerates commissioning and service.

TOLL

Access XL2/XXL

Barriers for wide lanes

- > Large barrier width of up to 10.0 m
- > High security with optional barrier boom skirt
- > Very low operating costs thanks to efficient and long-lived MHTM™ drive
- > Ease-of-use and optimum accessibility thanks to well thought-out design
- > Legal security with Declarations of Conformity and Performance
- > Designed for 2 million opening and closing actions



Technical data	Access XL 2	Access XXL
Lane width	Max. 8.5 m	Max. 10.0 m
Opening/closing time	6.0 s	8.0 s
Power consumption	Max. 17 W	Max. 30 W
Drive technology	MHTM™	MHTM™
Voltage	85 – 264 VAC, 50/60 Hz	85 – 264 VAC, 50/60 Hz
Duty cycle	100 %	100 %
Housing dimensions (W x D x H)	435 x 360 x 1164 mm	435 x 360 x 1164 mm
Enclosure rating	IP 54	IP 54
Temperature range	−30 to +55 °C	−30 to +55 °C
Weight	105 kg	112 kg


Features	Access XL 2	Access XXL
Standard colours	RAL 2000	RAL 2000
Barrier arm	MicroBoom XL	MicroBoom XL
Control system	MGC Pro	MGC Pro
Integrated 2-channel detector for induction loops	Standard	Standard
Modular expansion of control system	Standard	Standard
Variable I/O assignment	Standard	Standard
No. of digital inputs	8	8
No. of relays/digital outputs	6/4	6/4
Input with test for safety light barrier/Laser scanner	Standard	Standard
Selectable closing speed	Standard	Standard
Selectable opening speed	Standard	Standard

Options	Access XL2	Access XXL
Special colours	\checkmark	1
Standard boom skirt	\checkmark	✓
Boom skirt with climb-over prevention (height = 1.30 m)	✓ (Up to 6 m boom length)	\checkmark (Up to 6 m boom length)
Boom skirt with climb-over prevention (height = 1.80 m)	✓ (Up to 6 m boom length)	\checkmark (Up to 6 m boom length)
Pendulum support*	\checkmark	~
Support post*	\checkmark	✓
Boom interlock	\checkmark	1
Boom illumination, red ¹	\checkmark	1
Light strips, red/green ²	\checkmark	1
Hood light	\checkmark	1
Key-operated switch	\checkmark	\checkmark
Radio module	\checkmark	\checkmark
Ethernet module	\checkmark	1
RS485 module	\checkmark	✓
CAN module (counting)	\checkmark	✓
Second detector module	\checkmark	\checkmark
GSM module	\checkmark	✓
Safety light barrier/Laser scanner	\checkmark	\checkmark


 * Both models must be supported with a pendulum support or with a support post.

¹ With climb-over prevention only possible on the back of the barrier boom ² Not in combination with standard boom skirt

Dimensional drawings



From a passage width (D) of more than 6 m





Access to Progress

Magnetic stands for pioneering products – in every way. Our access control systems for vehicles or pedestrians clear the way for thousands of people every day – at car parks, toll gates, stations, airports and in buildings. Our technology is also pioneering, however: with innovative drives, intelligent control systems and well thought-out details it provides maximum safety and longevity. Are you also on the path to Magnetic?



Vehicle barriers

Access barriers Parking barriers Toll barriers Special barriers

Germany MAGNETIC AUTOCONTROL GMBH Grienmatt 20 79650 Schopfheim Phone +49 7622 695-5 Fax +49 7622 695-800 E-mail info@magnetic-germany.com

Australia MAGNETIC AUTOMATION PTY LTD 38 Metrolink Circuit Campbellfield, VIC 3061 Phone +61 3 9339 2900 E-mail info@magnetic-oz.com

Austria FAAC GMBH Münchner Bundesstraße 123 5020 Salzburg Phone +43 662 853395-0 E-mail at.info@faacgroup.com

Benelux countries FAAC BENELUX NV/SA

Industriezone 3B 8490 Jabbeke Belgium Phone +32 50 320202 E-mail info@magnetic-benelux.com



Pedestrian gates

Turnstiles Swing gates Tripod gates Retractable gates Wing gates

Brazil

MAGNETIC AUTOCONTROL LTDA Av. Salim Antônio Curiati, 136 04690-050 – São Paulo Phone +55 11 5660 8500 E-mail info@magnetic-br.com

China

MAGNETIC CONTROL SYSTEMS CO., LTD No. 3 Building, No. 51

Lane 1159, Kang Qiao (East) Road Kang Qiao Industrial Zone, Shanghai Phone +86 21 68182970 E-mail info@magnetic-cn.com

France FAAC FRANCE 377 Rue Ferdinand Perrier 69808 St Priest Cedex Phone +33 4 72 21 86 89 E-mail info@magnetic-fr.com

India MAGNETIC FAAC INDIA PVT LTD. PRS Centre Plot No. 373 to 376, 2nd Floor (West Wing)

1st Cross Street, Nehru Nagar Old Mahabalipuram Road Kottivakkam (Opp Rayala Technopark, Perungudi) Chennai 600041 Phone +91 44 421 23297 E-mail info@magnetic-india.com



Terminals ^{Cars} Trucks

Middle East FAAC MIDDLE EAST FZE Dubai Silicon Oasis PO Box 54886 Dubai United Arab Emirates Phone +971 4 3724193 E-mail info@magnetic-uae.com

N. and S. America (excl. Brazil) FAAC INTERNATIONAL, INC 3160 Murell Road Rockledge, FL 32955 USA Phone +1 321 635 8585 E-mail info@magnetic-usa.com

Scandinavia FAAC NORDIC AB Box 125 284 22 Perstorp Sweden Phone +46 435 77 95 03 E-mail info@magnetic-nordic.com

Southeast Asia

MAGNETIC CONTROL SYSTEMS SDN. BHD No. 17, Jalan Anggerik Mokara 31/54 Taman Perindustrian Kota Kemuning 40460 Shah Alam Selangor Darul Ehsan Malaysia Phone +60 3 5123 0033 E-mail info@magnetic-malaysia.com

